

PRODUCT TYPE		GPON ONT	MODEL: G110R	
HARDWARE	CPU	CPU Feature	Single core,MIPS interAptiv™1GHz	
	Interfaces	LAN port	1* GE port	
		PON port	1	
		DC port	1	
		Reset	1	
		Wi-Fi	Standard	IEEE 802.11 b/g/n
	Speed		300Mbps @ 2.4GHz 2T2R	
	Antenna		2* External	
	Gain		5dBi	
	GPON	Standard	ITU-T G.984/G.988	
		Wavelength	1310nm/1490nm	
		Speed	Upstream rate up to 1.244 Gbit/s, downstream rate up to 2.488 Gbit/s	
		Sensitivity	≤-28dBm	
		Emission Power	1dBm<P<4dBm	
		Distance	20 km	
		Connector	SC/UPC or SC/APC	
SOFTWARE	Support	Protocols	ITU-T G.984/G.988 IEEE 802.1D, Spanning Tree IEEE 802.1Q, VLAN IEEE 802.1w, RSTP IGMP v1/v2/v3 ITU-T Y.1291	
		Access Mode	Optional: PPPoE, Bridge, IPoE	
		Management	OMCI, TR-069(FreeAcs、GenieAcs)	
		Algorithm	SP/WRR/SP+WRR	
	Security	Encryption	AES128	
		Authentication	CHAP, EAP	
		Others	Loopback	
	OTHERS	Accessories	1 * Power Adaptor	
1 * Manual				
Device Parameter		Power Supply	Input 110~240VAC; Output 12VDC/1A	
		Power Consumption	<12W	
		Net Weight	115g	
		Size	147mm(L)*92mm(W)*24.5mm(H)	